



# BEARING DRIVESHAFT, INC.



60 mm x 115 mm x 39 mm KOYO T2EE060 tapered roller bearings

Bearing No. T2EE060

T2EE060 Bearing 2D drawings and 3D CAD models

Size	60x115x40 mm
Bore Diameter	60 mm
Outer Diameter	115 mm
Width	40 mm
d	60 mm
D	115 mm
T	40 mm
B	39 mm
C	33 mm
a	27,6 mm
r min.	2,5 mm
r2 min.	2,5 mm
da min.	72 mm
da max	70 mm
Da min	98 mm
Da max.	103 mm
Db min.	109 mm
ra max.	2 mm
rb max.	2 mm
Weight	1,8 Kg
Basic dynamic load rating (C)	183 kN
Basic static load rating (C0)	242 kN
(Grease) Lubrication Speed	3400 r/min
(Oil) Lubrication Speed	4600 r/min
Calculation factor (e)	0,33



## BEARING DRIVESHAFT, INC.

Calculation factor (Y0)	0,99
Bearing No.	T2EE060
r(min)	2.5
r1(min)	2.5
Cr	229
C0r	242
Cu	37.7
Grease lub.	3400
Oil lub.	4600
a	27.6 mm
da(min)	72
db(max)	70
Da(max)	103
Da(min)	98
Db(min)	109
Sa(min)	6
Sb(min)	7
ra(max)	2
rb(max)	2
e	0.33
Y1	1.80
Y0	0.99
(Refer.) Mass(kg)	1.80