



# BEARING DRIVESHAFT, INC.

## KOYO K15X19X10 needle roller bearings



K15X19X10 Bearing 2D drawings and 3D CAD models

Bearing No. K15X19X10

Bore Diameter	15 mm
Outer Diameter	19 mm
Fw	15 mm
Ew	19 mm
Bc	10 mm
Weight	0.005 Kg
Basic dynamic load rating (C)	7.87 kN
Basic static load rating (C0)	9.69 kN
(Grease) Lubrication Speed	18000 r/min
(Oil) Lubrication Speed	28000 r/min
Category	Needle Non Thrust Roller Bearings
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.005
EAN	0060579020445
Product Group	B04144
Rolling Element	Needle Roller Bearing
Component	Roller Assembly Only
Enclosure	Not Applicable
Self Aligning	No
Retainer	Yes
Number of Rows of Rollers	Single Row
Separable	No
Closed End	Not Applicable



## BEARING DRIVESHAFT, INC.

Inch - Metric	Metric
Thrust Bearing	No
Long Description	15MM Bore; 19MM Outside Diameter; 10MM Width; Needle Roller Bearing; Roller Assembly Only; No Self Aligning; Retainer; Single Row of Rollers; No Separable
Other Features	Radial Roller   Steel Cage
Category	Needle Non Thrust Roller Bearing
UNSPSC	31171512
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Needle
Manufacturer URL	<a href="http://www.koyousa.com">http://www.koyousa.com</a>
Manufacturer Item Number	K15X19X10
Weight / LBS	0.011
Outside Diameter	0.748 Inch   19 Millimeter
Bore	0.591 Inch   15 Millimeter
Width	0.394 Inch   10 Millimeter
Bearing No.	K15X19X10
Cr	7.87
C0r	9.69
Cu	1.45
Grease lub.	18000
Oil lub.	28000
P/S	S
(Refer.)Mass(kg)	0.005
Shaft(max.)	15.000
Shaft(min.)	14.992
Housing(max.)	19.020
Housing(min.)	19.007



# BEARING DRIVESHAFT, INC.