



BEARING DRIVESHAFT, INC.



6003ZZNR Bearing 2D drawings and 3D CAD models

17,000 mm x 35,000 mm x 10,000 mm NTN
6003ZZNR deep groove ball bearings

Bearing No. 6003ZZNR

Size	17x35x10 mm
Bore Diameter	17,000 mm
Outer Diameter	35,000 mm
Width	10,000 mm
d	17,000 mm
D	35,000 mm
B	10,000 mm
C	10,000 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.1
EAN	4547359010244
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	17MM Bore; 35MM



BEARING DRIVESHAFT, INC.

	Outside Diameter; 10MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Ste
Other Features	Deep Groove With Snap Ring
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Weight / LBS	0.08598
Outside Diameter	1.378 Inch 35 Millimeter
Bore	0.669 Inch 17 Millimeter
Outer Race Width	0.394 Inch 10 Millimeter
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	17 mm
precision rating:	ISO Class 0
outside diameter:	35 mm
finish/coating:	Uncoated
overall width:	10 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
inner ring width:	10 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	10 mm
snap ring included:	With Snap Ring



BEARING DRIVESHAFT, INC.

maximum rpm (grease):	20000 rpm
internal clearance:	CN
fillet radius:	0.3 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	24000 RPM
dynamic load capacity:	6800 N
series:	60
static load capacity:	3350 N
manufacturer product page:	Click here