




BEARING DRIVESHAFT, INC.

30,000 mm x 62,000 mm x 16,000 mm NTN
CS206LLU deep groove ball bearings



Bearing No. CS206LLU

CS206LLU Bearing 2D drawings and 3D CAD models

Size	30x62x16 mm
Bore Diameter	30,000 mm
Outer Diameter	62,000 mm
Width	16,000 mm
d	30,000 mm
D	62,000 mm
B	16,000 mm
C	16,000 mm
Category	Insert Bearings Spherical OD
Inventory	4.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.2
EAN	4547359056785
Product Group	M06110
Inner Race Profile	Standard Inner Ring
Outer Race Profile	Spherical
Relubricatable	No
Seal Type	Contact
Mounting Method	Shaft Mount
Rolling Element	Ball Bearing
Snap Ring	No
Long Description	30MM Bore; Standard Inner Ring; Ball Bearing; 16MM Length Thru Bore; 16MM Outer Race Width; 62MM



BEARING DRIVESHAFT, INC.

	Outside Diameter; Not Relubricatable; Contact Seal; Shaft Mount Mounting Method; No Snap Ring
Inch - Metric	Metric
Other Features	Single Row Light Duty Metric
Category	Insert Bearings
UNSPSC	31171536
Harmonized Tariff Code	8482.10.50.00
Noun	Bearing
Keyword String	Insert
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	CS206LLU
Weight / LBS	0.441
Bore	1.181 Inch 30 Millimeter
Outer Race Width	0.63 Inch 16 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter
Length Thru Bore	0.63 Inch 16 Millimeter
bore diameter:	30 mm
static load capacity:	10300 N
outside diameter:	62 mm
precision rating:	Class 0
overall width:	16 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	Through Hardened Steel
closure type:	Double Sealed
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	16 mm
snap ring included:	Without Snap Ring
outer ring width:	16 mm



BEARING DRIVESHAFT, INC.

internal clearance:	CN
fillet radius:	1 mm
operating temperature range:	-40 to 120 ° C
series:	CS2
dynamic load capacity:	15000 N
manufacturer product page:	Click here