




## BEARING DRIVESHAFT, INC.

69,85 mm x 101,6 mm x 19,05 mm NTN 4T-L713049/L713010 tapered roller bearings



Bearing No. 4T-L713049/L713010

4T-L713049/L713010 Bearing 2D drawings and 3D CAD models

Size	69.85x101.6x19.05 mm
Bore Diameter	69,85 mm
Outer Diameter	101,6 mm
Width	19,05 mm
d	69,85 mm
D	101,6 mm
T	19,05 mm
B	19,05 mm
C	15,083 mm
a	21.7 mm
rs min	1.57 mm
r1s min	1.57 mm
e	0.46
Y2	1.3
Y0	0.72
Mass	0.51 kg
Dynamic load, C	60.5 kN
Rating life coefficient, A2	1.4
Static load, C0	106 kN
Nlim (oil)	4,400 rpm
Nlim (grease)	3,300 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage	0.47 Hz



## BEARING DRIVESHAFT, INC.

frequency, FTF	
Characteristic rolling element frequency, BSF	13.99 Hz
Characteristic outer ring frequency, BPF0	15.84 Hz
Characteristic inner ring frequency, BRFI	18.16 Hz
ra max	1.5 mm
r1a max	1.5 mm
Category	Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.53
EAN	0692314623275
Product Group	B04334