



BEARING DRIVESHAFT, INC.

25,4 mm x 50,8 mm x 14,26 mm NTN
4T-07100S/07210X tapered roller bearings



Bearing No. 4T-07100S/07210X

4T-07100S/07210X Bearing 2D drawings and 3D CAD models

Size	25.4x50.8x15.011 mm
Bore Diameter	25,4 mm
Outer Diameter	50,8 mm
Width	15,011 mm
d	25,4 mm
D	50,8 mm
T	15,011 mm
B	14,26 mm
C	12,7 mm
a	18 mm
rs min	1.5 mm
r1s min	1.5 mm
e	0.4
Y2	1.49
Y0	0.82
Mass	0.13 kg
Dynamic load, C	26 kN
Rating life coefficient, A2	1.4
Static load, C0	28 kN
Nlim (oil)	10,000 rpm
Nlim (grease)	7,500 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage	0.42 Hz



BEARING DRIVESHAFT, INC.

frequency, FTF	
Characteristic rolling element frequency, BSF	6.27 Hz
Characteristic outer ring frequency, BPF0	7.22 Hz
Characteristic inner ring frequency, BRFI	9.78 Hz
ra max	1.5 mm
r1a max	1.5 mm